



# Camera Cable T18

MINI-RAD CAMERA CABLE

ahlbergs.staging.westart.se/products/cables/camera-cable-t18



The T18 cable is designed to fit the Mini-Rad cameras. It is a flexible cable that can support the camera hanging solely by its cable.

# MORE INFORMATION ABOUT CAMERA CABLE T18

### **APPLICATIONS**

• Cable for underwater use or in air together with the Mini-Rad cameras

#### **BENEFITS**

• Equipped with a reterminable connector for use in air and a molded connector for underwater use

## **SPECIFICATIONS**

#### PHYSICAL CHARACTERISTICS

| Width  | 7 mm                    |
|--|-------------------------|
| Minimum Bend<br>Radius, Flexible<br>Installation | 80 mm                   |
| Outer sheath                                     | PUR, frosted            |
| Color  | Black                   |
| Weight   | 0.08 kg/m, 0.053 lbs/ft |
| Tensile Strength                                 | 800 N                   |
| Number of conductors                             | 18                      |

#### **ENVIRONMENTAL TOLERANCES**

| Radiation<br>Tolerance (total<br>dose) | 2 000 000 Gy (200 000 000 rad)   |
|--|----------------------------------|
| Temperature<br>Rating                  | -40°C to +80°C (-40°F to +176°F) |
| Water Tightness                        | 5 bar                            |

We reserve the right to alter specifications without prior notice



# **CAMERA CABLE T18 IMAGES**



We reserve the right to alter specifications without prior notice