

# Camera Cable T32

## MONOCHROME CAMERA CABLE

[ahlbergs.staging.westart.se/products/cables/camera-cable-t32](https://ahlbergs.staging.westart.se/products/cables/camera-cable-t32)



The T32 camera cable is used together with Ahlberg monochrome cameras. It is a flexible and strong cable specially designed with Kevlar braid for supporting the camera hanging solely by its cable.

## MORE INFORMATION ABOUT CAMERA CABLE T32

### APPLICATIONS

- Cable for underwater use or in air together with Ahlberg monochrome cameras

### BENEFITS

- A flexible and strong cable
- Can be equipped with a reterminable connector for use in air and a molded connector for underwater use
- Specially designed with Kevlar braid for supporting the camera hanging solely by its cable.

## SPECIFICATIONS

### PHYSICAL CHARACTERISTICS

Width	12 mm
Minimum Bend Radius, Flexible Installation	80 mm
Outer sheath	PUR, frosted
Color	Black
Weight	0.26 kg/m, 0.175 lbs/ft
Tensile Strength	5000 N
Number of conductors	30 + 2 coaxial

### ENVIRONMENTAL TOLERANCES

Radiation Tolerance (total dose)	2 000 000 Gy (200 000 000 rad)
Temperature Rating	-40°C to +80°C (-40°F to +176°F)
Water Tightness	3.5 bar

*We reserve the right to alter specifications without prior notice*

## CAMERA CABLE T32 IMAGES



*We reserve the right to alter specifications without prior notice*