



CCU890

CCTV CAMERA CONTROL UNIT

 $\underline{ahlbergs.staging.westart.se/products/camera-control-units/ccu890}$



The CCU890 is a versatile CCTV camera control unit that manages both pan-and-tilt functions and adjacent lighting units. It offers flexible operation, allowing control via a Pelco hand-held remote or integration with an external control system using Pelco protocol, ensuring seamless performance

MORE INFORMATION ABOUT CCU890

APPLICATIONS

- CCTV
- Under water inspections
- Hot Cell

BENEFITS

- CCTV camera control unit that supplies power and controls camera, pan-and-tilt, lighting and microphone units
- Control via a Pelco hand-held remote or external control system
- Controls both SD and HD cameras

BENEFITS

- · Supports camera cooling
- High temperature tolerant
- The unit can also be delivered in a high radiation tolerant version, CCU890HR

SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Width	400 mm
Length	300 mm
Height	157 mm
Weight	15 kg
Housing material	Stainless steel

ENVIRONMENTAL TOLERANCES

Operating	-20°C to +60°C (-4°F to +140°F)
Temperature	-20 C to +00 C (-4 F to +140 F)

POWER

Power Supply	100, 110, 120, 220 or 230VAC / 50-60 Hz / 500W
Lighting Power Supply	Yes

OUTPUTS

Video Outputs	Composite, SD, HD
External Lighting Output	2 channels

COMMUNICATION

Communication	Pelco D
Protocol	Pelco D

We reserve the right to alter specifications without prior notice

Main office | Phone: +46 176 20 55 00 Email: main@ahlbergcameras.com US office | Phone: +1 910-399-4240 Email: us@ahlbergcameras.com Service office | Phone: +46 176 20 55 00

Email: rd@ahlbergcameras.com




CCU890 IMAGES











We reserve the right to alter specifications without prior notice